
ATTENTION:

Miami, Tuesday, July 06, 2010

SUBJECT:


11Kw Diesel Generator Sets

We are pleased to present our line of SDMO Generators, the third largest genset manufacturer in the world:









Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions - Enclosed	Weight - Enclosed
480/277	11.2 / 14.0	10.2 / 12.7	16.8		
440/254	11.2 / 14.0	10.2 / 12.7	18.4	Length: 1750mm [69in]	535kg [1179lbs] Net
240/120	10.6 / 13.2	9.6 / 12.0	31.8	Width: 775mm [31in]	586kg [1292lbs] Gross
230/115	8.8 / 11.0	8.0 / 10.0	27.6	Height: 1230mm [48in]	000.19 [1.202.100] 0.000
220/127	11.2 / 14.0	10.2 / 12.7	36.7		
208/120	10.6 / 13.2	9.6 / 12.0	36.6		

SDMO TITUIV DIESEL GENERATOR SET

11Kw (14Kva) Standby, 10Kw (13Kva) Prime, 60Hz, 1800RPM, 3 Phase, 0.8 PF, 208/120V

- >MITSUBISHI S3L2.SD, Heavy duty diesel engine, 4 stroke, 1800rpm, Liquid cooled
- >MECC ALTE ECO3-3LN, brushless alternator. IP23 drip-proof protection, Insulation class H. Automatic voltage regulation.
- >MERLIN GERIN, Main line circuit breaker, 3pole, set mounted, wired and maximum output rated for complete generator protection
- >SDMO NEXYS, Digital auto-start control panel. All alarms, genset parameters, control functions and indicators, CE and UL compliant

STANDARD FEATURES

- >IP56 rated Weather proof, sound attenuated enclosure. 12 gauge electro zinc coated steel for maximum corrosion resistance
- >Auto Start control feature included for interoperation with ATS/AMF
- >Incorporated metallic fuel tank, single wall. High capacity: 50L (13Gal) (16hours @ 3/4)
- >12 lead reconnectable, single bearing alternator IP23, Insulation class H/H, AVR SR7+/- 1.0% regulation
- >Radiator for wiring Toof 50°C [122°F] max with mechanical fan
- >Microprocessor control panel
- >12V charging alternator and starter
- >12V charged DC starting battery with electrolyte and cables
- >29dB (A) Critical class silencer, muffler installed inside the canopy
- >Dry type air filter, fuel filter and oil filter elements installed
- >Mechanically welded chassis with vibration isolators
- >Each unit prototype and individually factory tested prior to shipping
- >User guide, commissioning and maintenance manual. Wiring diagrams included. (English, French and Spanish)
- >The generator accepts 100% rated load in one step as per NFPA110 and meets ISO8528-5 class G-3 for transient response
- >Compliant with ISO3046, ISO8528, BS4999, BS5514, BS5000PT99, AS1359, IEC34, UTE5100, VDE0530 and ISO9001:2000


Continues ...

ISO 9001

LAS GAUTH WAS CAUTH WAS COME TO SEE TO SE




Power Generation Solutions





ITSUBISHI



CONTROL PANEL

Auto Start



Nexys is a compact all-in-one unit designed for 1. Automatic engine start/stop, 2. Engine protection, 3. Breaker control, 4. Generator protection

Frequency meter, Ammeter, Voltmeter Alarms and faults Oil pressure, water temperature, Overcrank, Overspeed (>60 KVA), Min/max alternator, Low fuel level, Emergency stop Engine parameters Hours counter, Engine speed, Battery voltage, Fuel level, Air preheating, All other std features, please request catalog for details

PRICE:

OPTIONS1: OPTIONS2: OPTIONS3: 45 and COMPINED

- 11Kw Complete Generator set, "weather / sound proof" version as quoted - 1000Hours, Mitsubishi original filter kit for scheduled maintenance

- 12V automatic battery charger, installation included - Ocean transport and insurance charges to destination

LEAD TIME:

7-9 weeks, subject to previous sales. To be confirmed a time of order

PRICES:

US Dollars. Wire transfer or Cashier's check CREDIT CARD: 3% surcharge applies to credit card transactions

TERMS:

Prepaid to confirm order (OR) 50% to confirm order, 50% due prior to shipping

INCOTERMS:

EX Le Havre Port in France

WARRANTY: TESTING:

2 years limited warranty Standby duty or 2500 hours limited warranty Prime duty Each unit prototype and individually factory load bank tested prior to shipping COMPLIES TO: ISO3046, ISO8528, BS4999, BS5514, BS5000PT99, AS1359, IEC34, UTE5100,

VDE0530 and ISO9001:2000

ORDERS:

Orders are non cancellable, refundable nor exchangeable

VALIDITY:

45 days, subject to previous sales. This quotation is subject to typographical and technical corrections

arlos arrutia

Carlos Urrutia

Generator Sales Representative

Thank you for choosing General Power, your power generation solution



GENERAL POWER LIMITED. INC. 8145 N.W. 33rd Street / Miami, Florida 33122 (P) 305 471 9566 (P) 1 888 POWER58 (F) 305 471 9568 www.genpowerusa.com www.dieselgeneratorsmiami.com generators@genpowerusa.com



3430 Guayaquil Place

44132 Mercure Circle Sterling, VA 20166

Customer's Name / Address

GENERAL POWER LIMITED, INC

8145 NW 33 Street Miami, Florida 33122 P 305 471 9566 F 305 471 9568

PRO-FORMA INVOICE

Date	Invoice#	
8/2/2010	3420	
Ref	Incoterms	
A	EXW MIAMI	

Terms Due Date Rep Due on receipt 8/2/2010 CU

	VA 20166 3 4 232 7062	Due on receipt	8/2/2010		CU
Item	Description		Qty	Price	Total
TilUIV	SDMO T11UIV DIESEL GENERATOR SET 11KW (14KVA) STANDBY, 10KW (13KVA) PRIME, 60HZ, 1800 DIMENSIONS ENCL: 1750mm [69in] x 775mm [31in] x 1230mm >MITSUBISHI S3L2.SD, Heavy duty diesel engine, 4 stroke, 1800RJ >MECC ALTE ECO3-3LN, 4pole brushless alternator. IP23 drip-proceed voltage regulation >MERLIN GERIN, Main line circuit breaker, 3pole, set mounted, wir generator protection >SDMO NEXYS, Digital auto-start control panel. All alarms, genset pand UL compliant FULLY PACKAGED GENERATOR SET INCLUDES: >Weather proof, sound attenuated enclosure. 12 gauge electro zinc coal >Auto Start control feature included for automatic start/stop with ATS. Incorporated metallic fuel tank, single wall. High capacity: 50L / 130. >12 lead reconnectable, single bearing alternator IP23, Insulation class >Radiator for wiring Tof 50°C [122°F] max with mechanical fan >Microprocessor control panel >12V charging alternator and 12V starter motor >12V charged DC starting battery with electrolyte and cables >29dB(A) Critical class silencer, muffler installed inside the canopy >Dry type air filter, fuel filter and oil filter elements installed >Mechanically welded chassis with anti vibration isolators >Each unit prototype and individually factory load bank tested prior to User guide, commissioning and maintenance manual. Wiring diagram >The generator accepts 100% rated load in one step as per NFPA110 a >Compliant with ISO3046, ISO8528, BS4999, BS5514, BS5000PT94 ISO9001:2000	[48in], 586kg [1292lbs] Net PM, Liquid cooled of protection, Insulation class H. A red and maximum output rated for parameters, control functions and in the steel for maximum corrosion in AMF Gal (16hours @ ¾) is H/H, AVR SR7, +/- 1.0% regula shipping is included. (English, Spanish, Frei and meets ISO8528-5	Automatic complete indicators, CE resistance tion		
SP01 T11	SDMO T11U FILTER KIT. 500HOURS ORIGINAL MAINTENANCE KIT. SPARE PARTS FOI	R SCHEDULED SERVICE			
CHARGE	KOHLER CHARGERKIT/12V/UL AUTOMATIC BATTERY CHAI 12V, UL LISTED, AUTOMATIC BATTERY CHARGER KIT, REA	RGER KIT DY TO INSTALL			
SHIPPIN	GROUND TRANSPORT AND DELIVERY SERVICE TO MIAMI, FL 33178, DOOR TO DOOR SERVICE TO BUSINESS	WITH UNLOADING CAPABII	LITIES		

Phone 305 471 9566

Fax 305 471 9568

www.genpowerusa.com

Total



A 10.26

GENERAL POWER LIMITED, INC

8145 NW 33 Street Miami, Florida 33122 P 305 471 9566 F 305 471 9568

PRO-FORMA INVOICE

Date	Invoice#		
8/2/2010	3420		
Ref	Incoterms		
A	EXW MIAMI		

Customer's Name / Address

GSO 3430 Guayaquil Place 44132 Mercure Circle Sterling, VA 20166 P 011 593 4 232 7062

Terms Due Date Rep

Due on receipt 8/2/2010 CU

P 011 593	4 232 7062	Due on receipt	8/2/201	0	CU
Item	Description		and a	Qty Price	Total
T&C-EX	PRICES: U.S. Dollars QUANTITY: Prices reflected are for minimum quantity ordered AS LEAD TIME: 4-6 weeks for shipment preparation, after order confi TERMS: Irrevocable purchase order, 100% Due upon proof of deliv PAYMENT: Wire transfer subject to our confirmation. Company of subject to funds clearance (7 days approx.) INCOTERMS: EXW our BONDED warehouse Miami, FL PICK UPS: At our designated location. Flatbed may be required for Customs formalities and docs DISCOUNTS: Prices quoted reflect a 3% discount for Wire transfer are not eligible for this discount) NOTE: All wire transfer fees and charges MUST be paid by the cust ORDERS: All orders are non cancellable, non returnable, non excha authorization. Returns are subject to 35% cancellation/return fee over WARRANTY: Manufacturer's standard terms and conditions apply Please request instructions TAXES: 7% Florida Sales Tax not included. As applicable by law, of exemption/certificate, Please ask us VALIDITY: 45 days, subject to previous sales, typographical and ter Sales Tax	rmation, subject to previous sales/ery via ACH or wire transfer tecks, Cashier's checks and Perseloading. Bonded cargo is subject, Check or Cash payment (Crediomer ngeable without Our previous winvoice value. Subject to warranty registration tue prior to shipping or waived we	t to all U.S. t card payments ritten and guidelines.	7.009	0.00

Phone 305 471 9566

Fax 305 471 9568

www.genpowerusa.com

Total